


FLEXICS® S07BC4Q-F

PUR cable for submersible motor pumps, screened

DESIGN



- 1 | Bare copper conductors, fine wires class 5 according to DIN EN 60228 / VDE 0295 / IEC 60228
- 2 | Core insulation of special compound based on cross-linked polymer (XLPE)
- 3 | Cores are stranded together with optimal lay-length
- 4 | Plastic bonded aluminium tape and tinned copper wire braiding
- 5 | Special polyurethane (PUR) outer sheath, colour: yellow (RAL 1021)

APPLICATION

Extremely robust cable for extreme environmental conditions. The PUR outer sheath meets the highest requirements for tear and abrasion resistance. Excellent weather resistance, very good chemical resistance and microbial safe. Halogen-free and resistant to UV rays. Excellent EMC behavior.

TECHNICAL DATA



Rated voltage:
450/750 V (U₀/U)



Test voltage:
core / core 3000 V / 50 Hz



Temperature range:
operating temperature: -40 °C up to 90 °C
conductor temperature: max. 90 °C
short circuit temperature: max. 200 °C/5 s



Bending radius (min.):
fixed installation: 6 x Ø of cable
flexible use: 10 x Ø of cable



Core identification:
colours according to CENELEC HD 308 S2 or black (continuously numbered) with green/yellow ground conductor

Number of cores x nominal cross-section (mm ²)	Outer diameter (mm) appr.	Cu-value (kg/km)	Total weight (kg/km) appr.
FLEXICS® S07BC4Q-F			
4 G 1.5	10.7	99.0	150
5 G 1.5	11.9	117.0	180
7 G 1.5	14.0	165.0	245
12 G 1.5	17.8	258.0	404
16 G 1.5	19.8	326.0	488
7 G 2.5	15.8	247.0	330
4 G 4	14.9	228.0	301
4 G 6	17.3	317.0	423
4 G 10	22.4	530.7	739
4 G 16	26.0	782.0	1127

Technical changes reserved. All figures are therefore without guarantee.

14.1.2022, 15:57